

# 79 SERIES





#### **ULTRA SLIM**

New ultra-slim design with high gloss finish and ultra-narrow border

#### **ULTRA VIVID**

High-performance ultra vivid display Wide view AH-IPS panel

#### **ULTRA YOU**

Flicker-free technology for reduced eye fatigue MHL (Mobile High-Definition Link) support VGA + 2 x HDMI





















## 79 SERIES



### ➤ Features



#### **IPS Panel**

Experience superb picture quality with advanced IPS technology for brilliant, consistent color and wide viewing

#### AH-IPS Screen viewing angle of 178°





#### Flicker Free Backlight Technology

Most LED monitors use PWM (pulse width modulation) to control brightness; the pulsing creates flicker that may cause discomfort, headaches and eye strain, especially in low-light environments. Flicker Free technology uses a smooth DC (direct current) backlight system.





#### **Clear Vision**

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.





#### **Narrow Edge**

Ultra narrow bezel 2 mm bezel 9 mm panel black matrix





#### Screen +

The bundled Screen+ software splits the PC workspace into four self-contained panes to group application windows for easier viewing. Screen+ also supports multiple monitors.





#### MHL - Mobile High-Definition Link **Multimedia-Ready with HDMI Input**





## Specifications

Models	I2579VM
Panel size	25"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Contrast Ratio	1000:1 (Typical)
	50,000,000:1 (DCR)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Color	16.7M
Viewing Angle (H/V)	178/178
Viewable Image Size (mm)	633
Display Area	552.96(H)×308.64 (V)mm
Pixel Pitch (mm)	0.288
Scan Frequency (H/V)	30-83KHz/ 50-76Hz
Pixel Frequency	148.5MHz
Input Signal	Analog & HDMI*2(MHL)
Input Connector	Analog & HDMI*2(MHL)
Built-in Speaker	No
HDCP Compatible	YES
Input Power	110-240VAC, 50/60Hz
Power Supply	External
Operation Mode (W)	30W
Stand by Mode (W)	<0.5W
Wall-Mount	No
Cabinet Color	Black & Silver
Phys. (W×H×D) mm	576.9x427x138.2
Package Box (W×H×D) mm	640x490x140
Weight (Net/Gross) (kg)	4.5/6.41
Tilt	-3.5°~23.5°
Kensington lock	YES
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Menu/Enter, Clear Vision/<,
	Image Ratio/>, Source/Auto/Exit, Power
OSD Languages	16 Languages
	CE, FCC, CCC, TUV-Bauart, cTUVus,
Safety Regulation	CEL, CH RoHS, KC, KCC,
	ISO9241-307, C-Tick N26268,
	e-Standby, VCCI, J-Moss, PSE, PSB