

AOC

www.aoc.com



See it. Live it. In New Dimension.



D2757PH

57 LED SERIES

3D



■ Features



Flicker Free 3D Monitor with Polarized Glasses

Flicker Free 3D technology adopts passive glasses for stereo 3D display. Instead of rapidly switching each eye on and off, polarized glasses display continuous images, using a different pattern for the left and right eyes, providing a pleasant viewing experience with vivid 3D images and a wide viewing angle.



Support 2D to 3D

Enjoy a simulated 3D view of any 2D content, with Hot Key control.



LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



Narrow edge

Ultra Narrow Bezel 5.8mm



Detachable stand

Standard Monitor or Photo Frame Style.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.



Direct Insert I/O

Direct insert connectors face the rear, making it easier to connect the monitor to power and input sources.



Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.



EPA 5.0

Low power consumption meets the EPA Energy Star 5.0 standard.

■ Specifications

Model Name	D2757PH
Screen Size	27"W
Viewable Image Size	68.56cm
Pixel Pitch	0.311(H)×0.311 (V)mm
Display Area	597.6(H)×336.15 (V)mm
Brightness 2D	250 cd/m ²
Brightness 3D	95 cd/m ²
Contrast Ratio (typical)	20,000,000:1 (DCR)
Response Time (typical)	5ms
Viewing Angle	178/178 (CR≥10)
3D Viewing Angle	U/D 12 (3D CT<10)
3D Watching Distance	90cm (Typical)
Scan Frequency	H: 30K~83KHz V: 50~76Hz
Pixel Frequency	144MHz
Recommended Resolution	1920×1080@60Hz
Display Colours	16.7M
HDCP Compatible	Yes
Input Signal	Analog RGB, HDMI*2
Input Connector	15-pin D-Sub and HDMI*2
Power Supply	110~240VAC, 50/60Hz
Power Consumption	Power On: <40W (Typical), Standby: <0.5W
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	3D/<, Volume/>, Source/Auto/Exit, Power, Menu
OSD Languages	16Languages
Speakers	Yes
Safety & Regulations	BSMI, VCCI, PSE, J-Moss, MEPS, KCC, e-Standby, FCC, cCSAus, CE, EPA 5.0, Windows 7, RoHS
Wall-Mount	NA
Cabinet Colour	Black & Silver
W×H×D (w/base)mm	622× 499 ×130
W×H×D (package)mm	714×140×490
Weight (Net /Gross)	5.7kg/7.95kg