

INTENSELY LED.
INCREDIBLY INTELLIGENT.



70 SERIES MONITOR

- LED: Low Power Consumption
- Hair-Line Texture Design
- High DCR 20M:1
- e-Saver/i-Menu/Screen+ Software



E2270SWDN



◇ Features



LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



e-Saver

Software enables the user to set a low power configuration of the monitor when the PC is in screen saving, PC off, and user absence. User can choose the time to turn the monitor off, to save power consumption.



Screen+ Software

The bundled Screen+ software splits the PC workspace into four self-contained panes to group application windows for easier viewing. Screen+ also supports multiple monitors.



Narrow Edge

Ultra Narrow Bezel 12.6mm.



Hair-Line Texture

Brushed surface textures provide a luxury look and feel.



i-Menu

Included PC software allows the user to change the OSD settings using their mouse.



Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.

◇ Specifications

Model Name	E2270SWDN
Panel size	21.5"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Contrast Ratio	600:1 (Typical) 20,000,000:1 (DCR)
Brightness (Typical)	200 cd/m ²
Display Color	16.7M
Viewing Angel (H/V)	90/65
Viewable Image Size (mm)	547
Display Area	476.64 (H)×268 (V)mm
Pixel Pitch (mm)	0.248
Scan Frequency (H/V)	30-83KHz/ 50-75Hz
Pixel Frequency	108MHz
Input Signal	Analog & DVI
Input Connector	Analog & DVI
Cable	VGA
Built-in Speaker	N/A
HDCP Compatible	YES
Input Power	100-240VAC, 50/60Hz
Power Supply	Build- in
Operation Mode (W)	17W
Stand by Mode (W)	<0.5W
Wall- Mount	VESA 100x100mm
Cabinet Color	Black
Phys. (W×H×D) mm	503×407×115
Package Box (W×H×D) mm	558×394×108
Weight (Net/ Gross)(Kg)	2.7/3.45
Tilt	-3°~10°
Kensington Slot	YES
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Power/Auto
USB Plug	N/A
OSD Languages	16 languages
Safety Regulation	CTUvus, FCC, CB/CE, EPA6.0, Windows 8, CCC, BSMI, RoHS

Design and Specifications are subject to change without notice.