

AOC

High precision

Ultra slim



81-F IPS Monitor

Flicker Free, IPS Technology
and Infinity Glass Design






► Features



IPS Panel

Experience superb picture quality with advanced IPS technology for brilliant, consistent color and wide viewing angles.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 50,000,000:1 displays darker images with more depth and detail.



i-Menu

i-Menu

Included PC software allows the user to change the OSD settings using their mouse.



Microsoft Windows 8 Compatible



Flicker Free Backlight Technology


Most LED monitors use PWM (pulse width modulation) to control brightness; the pulsing creates flicker that may cause discomfort, headaches and eye strain, especially in low-light environments. Flicker Free technology uses a smooth DC (direct current) backlight system.



Clear Vision

Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.



Narrow Edge

Narrow Edge

Ultra narrow bezel
2 mm bezel
9 mm panel black matrix



Screen +

The bundled Screen+ software splits the PC workspace into four self-contained panes to group application windows for easier viewing. Screen+ also supports multiple monitors.

► Specifications

Models	I2381FH
Panel size	23"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Contrast Ratio	1000:1 (Typical) 50,000,000:1 (DCR)
Brightness (Typical)	250 cd/m ²
Display Color	16.7M
Viewing Angle (H/V)	178/178
Viewable Image Size (mm)	584.2
Display Area	509.184(H)×286.416 (V)mm
Pixel Pitch (mm)	0.265(H) x 0.265(V)mm
Scan Frequency (H/V)	30-83KHz/ 50-76Hz
Input Signal	Analog & HDMI
Input Connector	Analog & HDMI
Built-in Speaker	N/A
HDCP Compatible	YES
Input Power	110-240VAC, 50/60Hz
Power Supply	External
Operation Mode (W)	28W
Stand by Mode (W)	<0.5W
Wall Mount	NA
Cabinet Color	Black & Silver
Phys. (W×H×D) mm	533x400x150
Package Box (W×H×D) mm	600x472x187
Weight (Net/Gross) (kg)	3/4.89
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Menu/Enter,Clear Vision/<, Volume/>, Source/Auto/Exit, Power
USB Hub	N/A
OSD Languages	16 Languages
Safety Regulation	CE, FCC, CCC, TUV-Bauart, cTUVus, CEL, CH RoHS, KC, KCC, e-Standby, ISO9241-307, C-Tick N26268, VCCI, J-Moss, PSE, PSB