



Less Border. More Fun.

69 SERIES

**In
Plane
Switching**

- ▶ Ultra Slim with Ultra Narrow Bezel Design
- ▶ New Generation AH-IPS Panel
- ▶ Clear Vision with more vivid image
- ▶ HDMI (MHL) & DisplayPort
- ▶ Built-in Stereo Speakers



I2369VM



■ Features



AH-IPS Panel for Wide Viewing Angle and Good Image Performance

- Wide View** – No changes in brightness or color from any viewing angle.
- Real Color** – Consistent, uniform color at all points on the screen.
- Solid Panel** – No trails, puddling or flashing from touching the screen.



LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



MHL – Mobile High-Definition Link

A single slim cable directly connects a mobile phone or other portable device for Full HD video and digital surround sound, with power and recharging provided by the monitor.



Displayport

DisplayPort is designed to be the future digital video and sound connection standard, capable of higher performance and convenience than older formats.



Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.



Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.



Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.



Eco Mode

Hotkey adjustment of display settings suit 5 different viewing styles: Text, Internet, Game, Movie and Sport

■ Specifications

Model Name	i2369VM
Panel size	23"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Typical Contrast Ratio	1,000:1
Contrast Ratio	20,000,000:1 (DCR)
Brightness (Typical)	250 cd/m ²
Display Color	16.7M
Viewing Angel (H/V)	178/178
Viewable Image Size (mm)	584.2
Display Area	509.184(H)×286.416 (V)mm
Pixel Pitch (mm)	0.265
Scan Frequency (H/V)	30-83KHz/ 50-76Hz
Pixel Frequency	170MHz
Input Signal	Analog, HDMI1(MHL), HDMI2 & DP
Cable	VGA
Built-in Speaker	2W*2/Audio in *1/Audio out*1
HDCP Compatible	YES
Input Power	110-240VAC, 50/60Hz
Power Supply	Built-in
Operation Mode (W)	35W
Stand by Mode (W)	<0.5W
Wall- Mount	VESA 75x75mm
Cabinet Color	Black
Phys. (W×H×D) mm	531.4x398x204
Package Box (W×H×D) mm	603x467x138
Weight (Net/ Gross)(Kg)	3.76/5.48
Kensington lock	YES
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Menu/Enter, Clear Vision/<, Volume/>, Source/Auto/Exit, Power
Usb plug	N/A
OSD Languages	16 Languages
Safety Regulation	CE, FCC, CCC, TUV-Bauart, cTUVus, CEL, CH ROHS, BSMI, KC, Ukrain Safety, EPEAT Gold, ISO9241-307, WEEE, C-Tick, VCCI, PSE, J-MOSS, E-standby, TCO6.0
Special Features	AH-IPS Panel, MHL/HDMI/DP connectivity, Clear Border Desgin, Directly input, Clear Vision, Off timer, e-saver, i- Menu, screen+, DPS

Design and Specifications are subject to change without notice.