



Art Of Colors

[www.aoc.com](http://www.aoc.com)

More Screen.  
More Connectivity.  
More You.



Ultra Narrow Border

I2477FWQ 23.8"

- Perfect Panel - AH-IPS
- Flicker Free for Eye Care
- Connectivity - MHL, HDMI 1.4a & DP 1.2
- Built-in Speakers





## ► Features



### AH-IPS Panel for Wide Viewing Angle and Good Image Performance

Wide View – No changes in brightness or color from any viewing angle.  
Real Color – Consistent, uniform color at all points on the screen.  
Solid Panel – No trails, puddling or flashing from touching the screen.



### Flicker Free Technology

Most LED monitors use PWM (pulse width modulation) to control brightness; the pulsing creates flicker that may cause discomfort, headaches and eye strain, especially in low-light environments. Flicker Free technology uses a smooth DC (direct current) backlight system.



### Narrow Bezel, Narrow Black Border

Ultra narrow bezel (2mm) with narrow black border(3.5mm).



### DisplayPort

DisplayPort is designed to be the future digital video and sound connection standard, capable of higher performance and convenience than older formats.



### Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing



### MHL – Mobile High-Definition Link

A single slim cable directly connects any MHL-compatible smartphone or other portable device for instant big-screen HD video and digital sound, with power and recharging provided by the monitor.



### Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



### i-Menu

Included PC software allows the user to change the OSD settings using their mouse.

## ► Specifications

Model Name	I2477FWQ
Panel Size	23.8"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Contrast Ratio	1000:1 (Typical) 50,000,000:1 (DCR)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Colors	16.7M
Viewing Angle (H/V)	178/178
Viewable Image Size (mm)	605
Display Area (mm)	527.04 (H) × 296.46 (V)
Pixel Pitch (mm)	0.2745
Scan Frequency (H/V)	30-83KHz/ 50-76Hz
Pixel Frequency	148.5MHz
Input Signals	Analog, HDMI1(MHL), HDMI2 & DP
Input Connectors	Analog, HDMI1(MHL), HDMI2 & DP
Built-in Speakers	3W, Audio out
HDCP Compatible	YES
Input Power	110-240VAC, 50/60Hz
Power Supply	External
Operating Power (W)	25W
Standby Power (W)	<0.5W
Wall Mount	75mmx75mm
Cabinet Color	Black & Silver
Phys. (W×H×D) mm	542.5x410x129
Package Box (W×H×D) mm	609x483x140
Weight (Net/Gross) (kg)	4.71/6.62
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Menu/Enter, Clear Vision/<, Volume/>, Source/Auto/Exit, Power
OSD Languages	16 Languages
Safety Regulation	CCC, FCC, cTUVus, CE, EPA, ISO9241-307, RoHS, Win7/8, BSMI, TCO6.0, KC, C-Tick, VCCI, J-Moss, e-Standby, PSB, PSE