



## Less Border. More Fun.

**69** SERIES

**In  
Plane  
Switching**

- ▶ Ultra Slim with Ultra Narrow Bezel Design
- ▶ New Generation AH-IPS Panel
- ▶ Clear Vision with more vivid image
- ▶ HDMI (MHL) & DisplayPort
- ▶ Built-in Stereo Speakers



I2769VM



## ■ Features



### AH-IPS Panel for Wide Viewing Angle and Good Image Performance

- Wide View** – No changes in brightness or color from any viewing angle.
- Real Color** – Consistent, uniform color at all points on the screen.
- Solid Panel** – No trails, puddling or flashing from touching the screen.



### LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



### Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



### Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



### MHL – Mobile High-Definition Link

A single slim cable directly connects a mobile phone or other portable device for Full HD video and digital surround sound, with power and recharging provided by the monitor.



### Displayport

DisplayPort is designed to be the future digital video and sound connection standard, capable of higher performance and convenience than older formats.



### Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.



### Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.



### Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.



### Eco Mode

Hotkey adjustment of display settings suit 5 different viewing styles: Text, Internet, Game, Movie and Sport

## ■ Specifications

Model Name	I2769VM
Panel size	27"
Screen Ratio	16:9
Response Time (Typical)	5ms
Recommended Resolution	1920x1080
Typical Contrast Ratio	1,000:1
Contrast Ratio	20,000,000:1 (DCR)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Color	16.7M
Viewing Angel (H/V)	178/178
Viewable Image Size (mm)	686
Display Area	597.888(H)×336.312 (V)mm
Pixel Pitch (mm)	0.3114
Scan Frequency (H/V)	30-83KHz/ 50-76Hz
Pixel Frequency	170MHz
Input Signal	Analog, HDMI1(MHL),HDMI2 & DP
Cable	VGA
Built-in Speaker	2W*2/Audio in *1/Audio out*1
HDCP Compatible	YES
Input Power	110-240VAC, 50/60Hz
Power Supply	Build- in
Operation Mode (W)	35W
Stand by Mode (W)	<0.5W
Wall- Mount	VESA 75x75mm
Cabinet Color	Black
Phys. (W×H×D) mm	622x449x130
Package Box (W×H×D) mm	710×538×159
Weight (Net/ Gross)(Kg)	4.99/7.23
Kensington lock	YES
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Menu/Enter, Clear Vision/<, Volume/>, Source/Auto/Exit, Power
Usb plug	N/A
OSD Languages	16 Languages
Safety Regulation	CE, cTUVus, FCC, CCC, EPA 6.0, CEL, KC, BSMI, ISO9241-307,TCO 6.0, C-Tick N26268, VCCI, PSE, J-MOSS, E-standby, TUV-Bauart, China-ROHS, TUV-S
Special Features	AH-IPS Panel, MHL/HDMI/DP connectivity, Clear Border Desgin, Directly input, Clear Vision, Off timer, e-saver, i- Menu, screen+, DPS

Design and Specifications are subject to change without notice.