

See it. Live it. In New Dimension.



E2357FH / I2757FH




57 LED SERIES




## ■ Features



### IPS Panel for Wide Viewing Angle and Good Image Performance (I2757FH only)

-  **Wide View** – No changes in brightness or color from any viewing angle.
-  **Real Color** – Consistent, uniform color at all points on the screen.
-  **Solid Panel** – No trails, puddling or flashing from touching the screen.



### LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



### Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.



### Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



### Narrow edge

Ultra Narrow Bezel 2mm (23" 5.8mm)



### Detachable Stand

Standard Monitor or Photo Frame Style.



### Glare Panel ( E2357FH only)

Glossy panel surface displays brighter, more vivid images.



### Direct Insert I/O

Direct insert connectors face the rear, making it easier to connect the monitor to power and input sources.



### Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



### Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.

## ■ Specifications

Model Name	E2357FH	I2757FH
Screen Size	23"W	27"W
Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
Contrast Ratio (typical)	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Response Time (typical)	2ms	5ms
Viewing Angle	170/160 (CR≥10)	178/178 (CR≥10)
Recommended Resolution	1920×1080@60Hz	1920×1080@60Hz
Display Colours	16.7M	16.7M
HDCP Compatible	Yes	Yes
Input Signal	Analog RGB, HDMI x 2	Analog RGB, HDMI x 2
Power Consumption	Power On: <40W (Typical), Standby: <0.5W	Power On: <40W (Typical), Standby: <0.5W
Plug & Play	DDC 2B/CI or VESA DDC2B™	DDC 2B/CI or VESA DDC2B™
User Control	Eco/<, Volume/>, Source/Auto, Power	Eco/<, Volume/>, Source/Auto, Power
OSD Languages	16Languages	16Languages
Speakers	Yes	Yes
Safety & Regulations	CB/CE, FCC, KCC, ISO 9241-307, BSMI, EPA, VCCI, PSE, J-MOSS, Windows 7, C-Tick, e-Standby	CB/CE, FCC, KCC, ISO 9241-307, BSMI, EPA, TCO5.0, VCCI, PSE, J-MOSS, Windows 7, C-Tick, e-Standby.
Cabinet Colour	Black & Silver	Black & Silver
Features	Narrow Edge 5.8mm, Ultra Slim, Glare Panel HDMI Connectivity	Narrow Edge 2mm, Ultra Slim, IPS panel HDMI Connectivity

Design and Specifications are subject to change without notice.