



MULTI-TOUCH MONITOR.

72 SERIES. 21,5"

Photo Frame Design,
 IR 10ps Touch,
 Entertainment,
 HD Webcam w/ Mic,
 Win8 Certification,
 USB 2.0 Hub,
 2Wx2 Speaker w/ housing



adjustable



10 - points touch

myDisplay

GET IN TOUCH WITH **10** FINGERS



Features



72P Multi-Touch Display

Multi-touch: 10-point multi-touch, Ideal for Win8, It is so friendly experience to use multi-touch for gaming, entertainment, photo management and so on.



The best sound quality

The extreme sound quality is by 2W x 2stereo speaker with housing.



Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles.



MHL– Mobile High-Definition Link

A single slim cable directly connects a mobile phone or other portable device for Full HD video and digital surround sound, with power and recharging provided by the monitor.



USB Hub

Easy to reach PC data via USB2.0 x 3 connect to your PC

Specifications

| Model Name | E2272PWUT |
|---------------------------|---|
| Panel size | 21.5" |
| Screen Ratio | 16:9 |
| Response Time (Typical) | 2ms |
| Recommended Resolution | 1920x1080 |
| Contrast Ratio | 1000:1 (Typical) 50,000,000:1 (DCR) |
| Brightness (Typical) | 220 cd/m ² |
| Display Color | 16.7M |
| Viewing Angle (H/V) | 170/160 |
| Viewable Image Size (mm) | 547 |
| Display Area (mm) | 476.64 (H)×268.1 (V) |
| Pixel Pitch (mm) | 0.24825 |
| Scan Frequency (H/V) | 30-83KHz/ 50-76Hz |
| Pixel Frequency | 170MHz |
| Input Signal | Analog & HDMI*2 (MHL) |
| Input Connector | Analog & HDMI*2 (MHL) |
| Cable | Analog, HDMI,MHL,USB & Audio Cable (By region) |
| Built-in Speaker | 2W/Audio In & out*1 |
| HDCP Compatible | YES |
| Input Power | 100-240VAC, 50/60Hz |
| Power Supply | External |
| Operation Mode (W) | 45W |
| Stand by Mode (W) | <0.5W |
| Wall- Mount | 75mm x75mm |
| Cabinet Color | Black & Silver |
| Phys. (W×H×D) mm | 521.9x321.4x43.7 |
| Package Box (W×H×D) mm | 410x587x117 |
| Weight (Net/ Gross)(Kg) | 3.93/5.5 |
| Tilt | -15°~57° |
| Kensington lock | YES |
| Temperature Operating | 0°C ~+40°C |
| Temperature Non-Operating | -25°C - 55°C |
| Plug & Play | VESA DDC2B™ & DDC2B/CI |
| User Control | source/Auto/exit, Clear Vision/<, Volume/>, Menu/Enter, Power |
| USB Plug | USB2.0*3 |
| OSD Languages | 16 Languages |
| Safety Regulation | cTUVus, CCC, FCC, CE, TUV-Bauart, BSMI, VCCI, C-Tick Win8 |

Design and Specifications are subject to change without notice.